

Serial No.: 10/055,208

RECEIVED  
CENTRAL FAX CENTER

AUG 18 2006

1 LISTING OF THE CLAIMS

2 CLAIMS

3 LISTING OF THE CLAIMS

4 CLAIMS

5 1. (currently amended) A computerized method comprising: executing a nested transaction for  
6 computing data in an execution environment supporting a flat transaction only, and wherein a  
7 nested transaction encapsulates between a first StartTransaction operation and a corresponding  
8 first EndTransaction operation on a first nesting level a hierarchy of one or more further  
9 StartTransaction operations and corresponding further EndTransaction operations on further  
10 nesting levels, wherein a StartTransaction operation starts a transaction; and wherein an  
11 EndTransaction operation ends a transaction; wherein a facade library provides access from an  
12 object oriented environment to a relational database system, having a transaction object  
13 comprises a depth counter, a CommitTransaction operation, and a RollbackTransaction operation  
14 as object methods, and said method further comprising performing a StartTransaction operation  
15 by,

16 checking whether said StartTransaction operation is on the first testing level of said  
17 nested transaction, and

18 issuing a corresponding StartTransaction operation within said execution environment  
19 only if said StartTransaction operation is on the first testing level of said nested transaction in the  
20 affirmative case but not otherwise.

21 2. (currently amended) A computerized method for executing a nested transaction for computing  
22 data in an execution environment supporting a flat transaction only according to claim 1, said  
23 method performing an EndTransaction operation by:

DOCKET NUMBER: CH920000005US1

2/12

Serial No.: 10/055,208

1 checking, in case said EndTransaction operation is a CommitTransaction operation  
2 successfully terminating a transaction, whether said EndTransaction operation is on said first  
3 nesting level of said nested transaction, and  
4 issuing a corresponding CommitTransaction operation within said execution environment  
5 only if said EndTransaction operation is on said first nesting level of said nested transaction in  
6 the affirmative case but not otherwise.

7 3. (currently amended) A computerized method for executing a nested transaction for computing  
8 data in an execution environment supporting a flat transaction only according to claim 2, said  
9 method performing an EndTransaction operation in case said EndTransaction operation is a  
10 RollbackTransaction operation aborting a transaction as unsuccessful, by issuing a corresponding  
11 RollbackTransaction operation within said execution environment independent from the nesting  
12 level of said RollbackTransaction operation.

13 4. (currently amended) A computerized method for executing a nested transaction for computing  
14 data in an execution environment supporting a flat transaction only according to claim 3, said  
15 method performing, once a RollbackTransaction operation has been executed within said nested  
16 transaction, any further StartTransaction operation or any further EndTransaction operation  
17 within said nested transaction independent from its nesting level by rejecting it as being in error  
18 without issuing a corresponding StartTransaction operation or a corresponding EndTransaction  
19 operation to the execution environment.

20 5. (currently amended) A computerized method for executing a nested transaction for computing  
21 data in an execution environment supporting a flat transaction only, and wherein a nested  
22 transaction encapsulates between a first StartTransaction operation and a corresponding first  
23 EndTransaction operation on a first nesting level a hierarchy of one or more further  
24 StartTransaction operations and corresponding further EndTransaction operations on further  
25 nesting levels, wherein a StartTransaction operation starts a transaction; and wherein an  
26 EndTransaction operation ends a transaction; and said method further comprising performing a  
27 StartTransaction operation by,

DOCKET NUMBER: CH920000005US1

3/12

Serial No.: 10/055,208

1 checking whether said StartTransaction operation is on the first testing level of said  
2 nested transaction, and  
3 issuing a corresponding StartTransaction operation within said execution environment  
4 only if said StartTransaction operation is on the first testing level of said nested transaction in the  
5 affirmative case but not otherwise;

6 said method performing an EndTransaction  
7 operation by:  
8 checking, in case said EndTransaction operation is a CommitTransaction operation  
9 successfully terminating a transaction, whether said EndTransaction operation is on said first  
10 nesting level of said nested transaction, and  
11 issuing a corresponding CommitTransaction operation within said execution environment  
12 only if said EndTransaction operation is on said first nesting level of said nested transaction in  
13 the affirmative case but not otherwise;

14 said method performing an EndTransaction operation in case said EndTransaction operation is a  
15 RollbackTransaction operation aborting a transaction as unsuccessful, by issuing a corresponding  
16 RollbackTransaction operation within said execution environment independent from the nesting  
17 level of said RollbackTransaction operation

18 said method performing, once a RollbackTransaction operation has been executed within said  
19 nested transaction, any further StartTransaction operation or any further EndTransaction  
20 operation within said nested transaction independent from its nesting level by rejecting it as  
21 being in error without issuing a corresponding StartTransaction operation or a corresponding  
22 EndTransaction operation to the execution environment; and

23 wherein said method:  
24 checks the nesting level of any of said StartTransaction or EndTransaction operations by  
25 a depth counter,  
26 increments said depth counter in the case of processing a StartTransaction operation, and

DOCKET NUMBER: CH920000005US1

4/12

Serial No.: 10/055,208

1           decrements said depth counter in the case of processing an EndTransaction operation  
2    which is a CommitTransaction operation, and  
3           sets said depth counter to zero or an invalid value in the case of processing an  
4    EndTransaction operation which is a RollbackTransaction operation.

5    6. (currently amended) A computerized method for executing a nested transaction for computing  
6    data in an execution environment supporting a flat transaction only according to ~~claim~~ claim 5,  
7    wherein:  
8           said method is performed by a facade library separate from said execution environment,  
9    and said execution environment is a database system, and  
10          said facade library provides access from an object oriented environment to said relational  
11    database system.

12   7. (currently amended) A computerized method for executing a nested transaction for computing  
13   data in an execution environment supporting a flat transaction only according to claim 6, wherein  
14   said facade library comprises a STORE object class providing access to said database system and  
15   said STORE object class providing said StartTransaction operation as one of its methods.

16   8. (currently amended) A computerized method for executing a nested transaction for computing  
17   data in an execution environment supporting a flat transaction only according to claim 7, said  
18   method performing said  
19   StartTransaction operation by creating a transaction object for further control of said nested  
20   transaction in case said StartTransaction operation is on the first nesting level

21   9. (currently amended) A computerized method for executing a nested transaction for computing  
22   data in an execution environment supporting a flat transaction only according to claim 8, wherein  
23   said transaction object comprises said depth counter, said CommitTransaction operation, and said  
24   RollbackTransaction operation as object methods.

DOCKET NUMBER: CH920000005US1

5/12

Serial No.: 10/055,208

1 10. (currently amended) A computer implemented system for executing a nested transaction for  
2 computing data in an execution environment supporting a flat transaction only, the nested  
3 transaction being tangibly embodied in a computer to perform execution of transactions, and  
4 wherein a nested transaction encapsulates between a first StartTransaction operation and a  
5 corresponding first EndTransaction operation on a first nesting level a hierarchy of one or more  
6 further StartTransaction operations and corresponding further EndTransaction operations ends a  
7 transaction; said system performing a StartTransaction operation, the system comprising.

8 means for checking whether said StartTransaction operation is on the first nesting level of  
9 said nested transaction, and

10 means for issuing a corresponding StartTransaction operation within said execution  
11 environment only if said StartTransaction operation is on the first nesting level of said nested  
12 transaction in the affirmative case but not otherwise.

13 11. (currently amended) A data processing program for execution in a data processing system  
14 comprising software code portions for performing a computerized method for executing a nested  
15 transaction for computing data in an execution environment supporting a flat transaction only,  
16 and wherein a nested transaction encapsulates between a first StartTransaction operation and a  
17 corresponding first EndTransaction operation on a first nesting level a hierarchy of one or more  
18 further StartTransaction operations and corresponding further EndTransaction operations on  
19 further nesting levels, wherein a StartTransaction operation starts a transaction; and wherein an  
20 EndTransaction operation ends a transaction; wherein a facade library provides access from an  
21 object oriented environment to a relational database system, having a transaction object  
22 comprises a depth counter, a CommitTransaction operation, and a RollbackTransaction operation  
23 as object methods, and said method further comprising performing a StartTransaction operation  
24 by,

25 checking whether said StartTransaction operation is on the first nesting level of said  
26 nested transaction, and

27 issuing a corresponding StartTransaction operation within said execution environment  
28 only if said StartTransaction operation is on the first nesting level of said nested transaction in  
29 the affirmative case but not otherwise.

DOCKET NUMBER: CH920000005US1

6/12

Serial No.: 10/055,208

1 12. (currently amended) A computer program product stored on a computer usable medium,  
2 comprising computer readable program means for causing a computer to perform a method  
3 executing a nested transaction in an execution environment supporting a flat transaction only,  
4 and wherein a nested transaction encapsulates between a first StartTransaction operation and a  
5 corresponding first EndTransaction operation on a first nesting level a hierarchy of one or more  
6 further StartTransaction operations and corresponding further EndTransaction operations on  
7 further nesting levels, wherein a StartTransaction operation starts a transaction; and wherein an  
8 EndTransaction operation ends a transaction; wherein a facade library provides access from an  
9 object oriented environment to a relational database system, having a transaction object  
10 comprises a depth counter, a CommitTransaction operation, and a RollbackTransaction operation  
11 as object methods, and said method further comprising performing a StartTransaction operation  
12 by,

13 checking whether said StartTransaction operation is on the first nesting level of said  
14 nested transaction,

15 and issuing a corresponding StartTransaction operation within said execution  
16 environment only if said StartTransaction operation is on the first testing level of said nested  
17 transaction in the affirmative case but not otherwise.

18 13. (currently amended) An article of manufacture comprising a computer usable medium having  
19 computer readable program code means embodied therein for causing execution of a nested  
20 transaction for computing data in an execution environment supporting a flat transaction only,  
21 the computer readable program code means in said article of manufacture comprising computer  
22 readable program code means for causing a computer to effect the steps of claim 1.

23 14. (previously presented) A program storage device readable by machine, tangibly embodying a  
24 program of instructions executable by the machine to perform method steps for, said method  
25 steps comprising the steps of claim 1.

DOCKET NUMBER: CH920000005US1

7/12

Serial No.: 10/055,208

1 15. (currently amended) An article of manufacture comprising a computer usable medium having  
2 computer readable program code means embodied therein for causing execution of a nested  
3 transaction for computing data in an execution environment supporting a flat transaction only,  
4 the computer readable program code means in said article of manufacture comprising computer  
5 readable program code means for causing a computer to effect the steps of claim 5.

6 16. (previously presented) A program storage device readable by machine, tangibly embodying a  
7 program of instructions executable by the machine to perform method steps for, said method  
8 steps comprising the steps of claim 5.

9 17. (currently amended) A computer program product comprising a computer usable medium  
10 having computer readable program code means embodied therein for causing a executing a  
11 nested transaction for computing data in an execution environment supporting a flat transaction  
12 only, the computer readable program code means in said computer program product comprising  
13 computer readable program code means for causing a computer to effect the functions of claim  
14 10.

15 18. (New) A computerized method for executing a nested transaction in an execution  
16 environment supporting a flat transaction only according to claim 1, said method performing an  
17 EndTransaction operation for computing data by:  
18 checking, in case said EndTransaction operation is a CommitTransaction operation  
19 successfully terminating a transaction, whether said EndTransaction operation is on said first  
20 nesting level of said nested transaction, and  
21 issuing a corresponding CommitTransaction operation within said execution environment  
22 only if said EndTransaction operation is on said first nesting level of said nested transaction;  
23 said method performing an EndTransaction operation in case said EndTransaction operation is a  
24 RollbackTransaction operation aborting a transaction as unsuccessful, by issuing a corresponding  
25 RollbackTransaction operation within said execution environment independent from the nesting  
26 level of said RollbackTransaction operation; and

DOCKET NUMBER: CH920000005US1

8/12

Serial No.: 10/055,208

1 said method performing, once a RollbackTransaction operation has been executed within said  
2 nested transaction, any further StartTransaction operation or any further EndTransaction  
3 operation within said nested transaction independent from its nesting level by rejecting it as  
4 being in error without issuing a corresponding StartTransaction operation or a corresponding  
5 EndTransaction operation to the execution environment.

6 19. (New) An article of manufacture comprising a computer usable medium having computer  
7 readable program code means embodied therein for causing execution of a nested transaction for  
8 computing data in an execution environment supporting a flat transaction only, the computer  
9 readable program code means in said article of manufacture comprising computer readable  
10 program code means for causing a computer to effect the steps of claim 18.

11 20. (New) A computerized method for executing a nested transaction in an execution  
12 environment supporting a flat transaction only according to claim 5, wherein:  
13 said method is performed by a facade library separate from said execution environment,  
14 and said execution environment is a database system, and  
15 said facade library provides access from an object oriented environment to said relational  
16 database system;  
17 said facade library comprises a STORE object class providing access to said database  
18 system and said STORE object class providing said StartTransaction operation as one of its  
19 methods;  
20 said method performing said StartTransaction operation by creating a transaction object  
21 for further control of said nested transaction in case said StartTransaction operation is on the first  
22 nesting level; and  
23 said transaction object comprises said depth counter, said CommitTransaction operation,  
24 and said RollbackTransaction operation as object methods.

DOCKET NUMBER: CH920000005US1

9/12